



# Q 70-250

## 2K HS AS Clearcoat 2:1 anti-scratch

### Characteristics

70-250 is a scratch-resistant High-filling 2-component acrylic clearcoat with UV protection, which ensures high gloss and protection on solventbased and water-based basecoats. Ideally suited for use in spot repair work as well as for complete paintwork. High resistance to weather, environmental influences and chemicals, resistant to yellowing, durable gloss retention. In addition, 70-250 Clear Coat provides excellent polishing properties.

### Physical Characteristics



12 month




n/a



2:1 + 0-10%  
70-205HN / 70-205HF

### Application



18 - 20 s  
4 mm DIN



1,2 - 1,3 mm  
2,0 - 2,2 bar

Consumption: 6 - 8 m<sup>2</sup>/l



1 - 2



Between the coatings  
Before the oven drying

5 - 10 min  
10 - 15 min



40 - 60 μm

### Drying



dust free: 30 - 40 min  
set to touch: 6 - 8 h  
ready for assembly 24 h

set to touch: 30 min  
ready for assembly 2 h

shortwave 8 Minuten  
mediumwave 10 - 15 Minuten

20°  
1 h with 70-205HF Hardener fast  
4 h with 70-205 HN Hardener normal

### Storage



Store the product in a ventilated place. Keep away from direct exposure to sunlight. Keep between +5°C and 20°C.

### Safety



For more informations check the safety data sheet.



This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacturing of our products. Copyright: Q-Company Int. GmbH, all rights reserved.